FD-4 Series Micro Security Radar

FD4-80CJ60

FD4-150CJ30

FD4-200DJ5

FD4-400CJ60



Sensor Coverage Comparison

FD4-80CJ60

FD4-150CJ30

FD4-200DJ5

FD4-400CJ30



XIAN FEIDA ELECTRONIC TECHNOLOGY CO.,LTD.

www.fdradar.com Email: feida_radar@126.com

FD-4 Series Micro Security Radar

TECHNICAL SPECIFICATIONS

SENSOR	FD4-80CJ60	FD4-120CJ30	FD4-200DJ5	FD4-400CJ30
MAX RANGE	Walker:80 meters	Walker:120 meters	Walker:200 meters	Walker:500 meters
	Vehicle:150 meters	Vehicle:200 meters	Vehicle:220 meters	Vehicle:600 meters
Center Frequency	24GHz±150M	24GHz±150M	24GHz±150M	9.8GHz±200MHz
Effective Field of	Horizontal: 60 degrees	Horizontal: 30 degrees	Horizontal: 5 degrees	Horizontal: 30 degrees
View	Vertical: 20 degrees	Vertical: 20 degrees	Vertical: 20 degrees	Vertical: 20 degrees
Angular Accuracy	±3 degrees	±1.5 degrees	5 degrees	±1.5 degrees
Range Resolution	1 meter	1 meter	1 meter	3meter
Update Rate	Up to 4 times per	Up to 4 times per	Up to 10 times per	Up to 4 times per second
	second	second	second	
Simultaneous	15	15	15	30
Tracks				
Output Data	velocity,RCS, range,	velocity,RCS, range,	velocity,RCS, range	velocity,RCS, range,
	angle	angle	of moving targets	angle
Interface	Ethernet	Ethernet	Ethernet	Ethernet
Physical Interface	Passive PoE through	Passive PoE through	Passive PoE through	Passive PoE through IP66
	IP66 RJ45 connector,	IP66 RJ45 connector,	IP66 RJ45 connector,	RJ45 connector, 10/100
	10/100 Mbps	10/100 Mbps	10/100 Mbps	Mbps
Rugged/Waterproof	IP66	IP66	IP66	IP66
System Power	10 Watts @ 8-16 VDC	10 Watts @ 8-16 VDC	10 Watts @ 8-16 VDC	15Watts @ 8-16 VDC



XIAN FEIDA ELECTRONIC TECHNOLOGY CO.,LTD. www.fdradar.com Email: feida_radar@126.com TEL:+862988339673 +8613992888943